

Generator

Whether it's continuous, prime or standby power that you require, PGT has started marketing & after sales service with world renowned Engines & Alternator from UK. USA. Japan & EU Countries. Engines are PERKINS of UK, Yanmar of Japan, Deutz of Germany, Volvo Penta of Sweden, John Deere of France /USA and Alternators are Meccalte of Italy/UK, Stamford, UK. We currently supply to the agricultural, Real State & Industry sector in all over Bangladesh with the range of 5KVA to 2000KVA.



MODELLO model	POTENZA Power - VA				MODELLO model	MOTORE/ Engine						SERBATOIO tank	DIMENSIONI dimensions			PESO weight	QUADRO ELETTRICO electric panel		INSONORIZZATO soundproof			
	CONT. PP		MAX TP			REG. gov	CIL. cyl.	CILIND. displac.	POTENZA power		CONSUMO consump.		L	L	A		Kg	MODELLO model	AUTOM. automatic	MODELLO model		
	33 Hz	63 Hz	50 Hz	60 Hz					33 Hz	60 Hz	33 Hz									60 Hz	L	mm
GP35A/P	30	/	33	/	1103C-3303	M	3	3300	41	/	6,1	/	70	1750	790	1100	780	M090	A060	T90	GP100A/P	
GP44A/P	40	/	44	/	1103C-33T03	M	3	3300	62	/	8	/	70	1750	790	1100	840	M090	A060	T90	GP100A/P	
GP66A/P	60	/	66	/	1104C-44T03	M	4	4410	83	/	10,2	/	100	2100	990	1300	940	M070	A070	T65	GP160A/P	
GP88A/P	80	/	88	/	1104C-44TAG1	E	4	4410	110	/	14,3	/	100	2100	990	1300	1080	M070	A070	T65	GP160A/P	
GP110A/P	100	112,5	110	125	1104C-44TAG2	E	4	4410	138	150	17,1	20,2	100	2100	990	1400	1210	M070	A070	T70	GP110A/P	
GP140A/P	130	/	143	/	1106C-66TAG2	E	6	6600	181	/	24,3	/	140	2850	1000	1400	1470	M070	A070	T80	GP140A/P	
GP160A/P	150	169	165	188	1106C-66TAG3	E	6	6600	199	219	27,5	30	140	2850	1000	1400	1500	M070	A070	T85	GP160A/P	
GP220A/P	200	231	220	253	1306C-88TAG3	E	6	8700	267	296	35	38,5	150	3000	1100	1500	1750	M085	A080	T85	GP220A/P	
GP280A/P	250	/	275	/	1306C-88TAG6	E	6	8700	330	/	36	/	150	3000	1100	1500	1910	M087	A080	T87	GP280A/P	
GP385A/P	350	/	385	/	2206C-E13TAG2	E	6	14600	473	/	52,5	/	300	3200	1300	2100	3260	M087	A080	/	T100SM GP385A/P	
GP480A/P	400	/	440	/	2206C-E13TAG3	E	6	14600	531	/	60,9	/	300	3200	1300	2100	3400	M087	A080	/	T100SM GP480A/P	
GP500A/P	450	/	495	/	2506C-E15TAG1	E	6	15200	605	/	73	/	300	3200	1300	2200	3430	M087	A080	T100S	GP500A/P	
GP500A/P	500	/	550	/	2506C-E15TAG2	E	6	15200	664	/	81	/	300	3200	1300	2200	3490	M087	A080	T100S	GP500A/P	
GP610A/P	550	/	605	/	2806C-E18TAG1A	E	6	18100	783	/	96	/	320	3400	1400	2200	4000	M087	A080	/	T112SM GP610A/P	
GP700A/P	650	/	715	/	2806A-E18TAG2	E	6	18130	833	/	97	/	500	3500	1600	2100	5150	M087	A080	T110S	GP700A/P	
GP810A/P	730	/	800	/	4006-23TAG2A	E	6	22921	866	/	113	/	500	3800	1700	2250	6230	M087	A080	T110S	GP810A/P	
GP880A/P	800	/	880	/	4006-23TAG3A	E	6	22921	1054	/	126	/	500	4000	1700	2010	6250	M087	A080	/	T130 GP880A/P	
GP1000A/P	905	/	996	/	4808TAG1A	E	8	30561	1176	/	148	/	500	4500	2000	2300	7700	M087	A080	/	T130 GP1000A/P	
GP1120A/P	1022	/	1125	/	4808TAG2A	E	8	30561	1320	/	159	/	600	5300	2100	2300	7800	M087	A080	/	T140 GP1120A/P	

Powered by:

